



The purpose-built, enterprise-class kiosk that re-defines the self-service experience.



Combining the power of a desktop computer and the user experience of a tablet, the Monarch is the *ideal* built-for-purpose kiosk designed for retail, hospitality and commercial applications.

The Monarch is powered by an Intel® 64-Bit processor, features a 10.1" display with capacitive touchscreen, and can be powered using a Power-over-Ethernet equipped wired network. Options include omni-directional barcode scanning and WiFi/BT communications.

The Monarch is the ultimate in power and versatility, unmatched by any other self-service kiosk in its class.



- Combines "consumer-friendly" with "enterprise-ready".
- 10.1" Color Display with Capacitive Touchscreen.
- Seamless enterprise integration and management.
- VESA 75 mounting for wall, pole or counter.
- Sleek form factor available in custom colors.
- HDMI output for supplemental digital signage.
- Powerful x86 architecture.



# Physical Specifications

Dimensions 267mm W x 211mm H x 47mm D 10.5" W x 8.3" H x 1.9" D

Weight 2.15 lbs / 0.98 kg

Display 10.1" LCD, 1280 x 800 resolution IPS Projective Capacitive Multi-touch

Mounting VESA 75mm standard mount pattern

Power 5VDC, PoE (802.3af and 802.3at)

I/O Ports USB 2.0 x 2

RJ45 Gigabit Ethernet with PoE

Mini PCI Express HDMI Output

Speaker Stereo 3W

Scan Engine 2D Imager

# Performance Specifications

Processor Intel® Atom™ E3825 1.33GHz 64-Bit Dual Core Processor

Operating Windows<sup>™</sup> Embedded 8.1, Windows<sup>™</sup> 10 Systems Android<sup>™</sup> Marshmallow, Linux Mint 17.x Mate

Memory (RAM) 2GB DDR3L 1066 MT/s

Internal Storage 30GB mSATA SSD

External Storage Micro SDHC capable up to 64GB

### Wireless Data Communications

WLAN Optional: 802.11abgn 2X2 with BT 4.0 Smart Ready

WWAN Optional: 4G LTE

# **Printer Accessory**

Roll Dimensions 2.25" (58mm) W x 1.25" OD (31.75mm)

Linerless Label 22ft/roll Diamond Pattern Adhesive

Thermal Paper 34ft/roll Coreless-design Rolls



# Optional Peripherals & Accessories

#### Power Adapter



#### Mounting Bracket



# **Environmental Specifications**

Operating Temp 0 to 40 C / 32 to 104 F

Storage Temp -20 to 60 C / -4 to 140 F

Humidity 5% to 90% (non-condensing)

# Standard Warranty

AML products are warranted against defects in material and workmanship under normal use and service for a period of one year from the date of purchase. The obligation of AML under this warranty is limited to furnishing labor and materials necessary to return the product to its normal operating condition, or to replace the unit, at AML's discretion, and only on a "return to factory" basis. This limited warranty does not extend to any product, which has been modified, misused, abused, or incorrectly installed. Warranty, also, does not extend to any product that has been repaired or altered by any party other than AML, or has been subjected to unusual physical or electrical stress, negligence or accident. Prior to returning a product for repair, the user must obtain a Return Authorization Number, which must be clearly marked on the outside of the shipping container.



Price Verification



Stock Check



**Videos** 



Virtual Visualizer



Expanded Product Info



Loyalty Programs



Gift Registry



Digital Catalog



Wayfinding



**Time Clock** 

Specifications are subject to change without notice. All names and products are the trademarks or registered trademarks of their respective organizations.

Windows is a registered trademark of Microsoft Corporation in the United States and other countries.



Corporate Headquarters 2190 Regal Parkway Euless, Texas 76040

Sales & Customer Service Tel: 800-648-4452 Fax: 817-685-6232 Email: sales@amltd.com www.amltd.com Local: 817-571-9015 Fax: 817-571-6176

Technical Support Tel: 877-842-3990 Fax: 817-685-6232 Email: support@amltd.com



© 2018 American Microsystems, Ltd.